

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : SM7108  
 Date Revised : 09/13/2017  
 Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** PERMATHANE SM7108 Polyurethane Sealant

#### MANUFACTURER

ITW Polymers Sealants North America  
 111 South Nursery Road  
 Irving, TX 75060

**Product Stewardship:** (972) 438-9111

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** PERMATHANE is a registered trademark of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Acute Toxicity (Inhalation), Category 3  
 Respiratory Sensitization, Category 1  
 Skin Sensitization, Category 1  
 Carcinogenicity, Category 2  
 Reproductive Toxicity, Category 1B  
 Target Organ Toxicity (Repeated exposure), Category 2  
 Aspiration Hazard, Category 1

##### Environmental:

Acute Hazards to the Aquatic Environment, Category 1  
 Chronic Hazards to the Aquatic Environment, Category 1

##### Physical:

Flammable Liquids, Category 4

#### GHS LABEL



Skull and  
crossbones



Exclamation  
mark



Health  
hazard



Environment

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H227: Combustible liquid.  
 H304: May be fatal if swallowed and enters airways.  
 H317: May cause an allergic skin reaction.  
 H331: Toxic if inhaled.  
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H351: Suspected of causing cancer.  
 H360: May damage fertility or the unborn child.  
 H373: May cause damage to organs through prolonged or repeated exposure.  
 H400: Very toxic to aquatic life.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017

Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

H410: Very toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENT(S)

#### Prevention:

- 80975E8A: P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260: Do not breathe dust/fume/gas/mist/vapours/spray.
- P271: Use only outdoors or in a well-ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P284: [In case of inadequate ventilation] wear respiratory protection.
- P273: Avoid release to the environment.

#### Response:

- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P302+P352: IF ON SKIN: Wash with plenty of water.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P311: Call a POISON CENTER or doctor
- P314: Get medical advice/attention if you feel unwell.
- P321: Specific treatment is required.
- P331: Do NOT induce vomiting.
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
- P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P362: Take off contaminated clothing.
- P370+P378: In case of fire: Use appropriate media to extinguish.
- P391: Collect spillage.

#### Storage:

- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P403+P235: Store in a well-ventilated place. Keep cool.
- P405: Store locked up.

#### Disposal:

- P501: Dispose of contents/container according to local, regional, national, and international regulations.

### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Liquid with a mild solvent odor

**IMMEDIATE CONCERNS:** CAUTION! Combustible liquid and vapor. Causes eye and skin irritation. Contains small amount of Toluene Diisocyanate (CAS No. 26471-62-5). May cause respiratory tract irritation. May cause allergic respiratory reaction. Harmful if inhaled. Respiratory sensitizer. May cause lung damage. Lung damage and respiratory sensitization may be permanent. May cause skin irritation. May cause allergic skin reaction. Skin sensitizer. Animal tests and other research indicate that skin contact with TDI can cause isocyanate desensitization and respiratory reaction.

### POTENTIAL HEALTH EFFECTS

**EYES:** Moderately irritating to the eyes.

**SKIN:** May cause mild skin irritation. Repeated or prolonged skin contact may result in allergic dermatitis.

**INGESTION:** Not likely route of entry. Harmful if swallowed, may cause nausea. Consult a physician.

**INHALATION:** May cause mild irritation to the respiratory tract. May aggravate existing respiratory conditions.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017

Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

**ROUTES OF ENTRY:** Eye and Skin Contact, Inhalation and Ingestion

**IRRITANCY:** Irritant to eyes, skin and respiratory tract.

**SENSITIZATION:** May cause allergic respiratory and skin reaction. Respiratory and skin sensitizer.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Butyl Benzyl Phthalate	10 - 20	85-68-7
Toluene	2 - 5	108-88-3
Toluene Diisocyanate	1 - 5	26471-62-5

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

**SKIN:** Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

**INGESTION:** Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

**INHALATION:** Under normal conditions of use, inhalation of product is unlikely. If fumes are inhaled and become irritant, remove person from the area to fresh air. Seek immediate medical attention if exposure has occurred.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Causes eye irritation.

**SKIN:** Contact causes skin irritation. Contains a component that is a skin sensitizer.

**INGESTION:** Not likely route of entry. May cause vomiting if ingested.

**INHALATION:** Respiratory tract irritation. Contains a component that is a respiratory sensitizer.

**ACUTE EFFECTS:** Irritant to the eyes, skin and respiratory tract.

**CHRONIC EFFECTS:** Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

**NOTES TO PHYSICIAN:** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Class IIIB

**GENERAL HAZARD:** Combustible Liquid.

**EXTINGUISHING MEDIA:** Use methods appropriate for the surrounding fire. Water spray, dry chemical, carbon dioxide, AFFF or alcohol resistant foams are all appropriate.

**OTHER CONSIDERATIONS:** This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point.

**EXPLOSION HAZARDS:** Solid water stream may spread fire. When exposed to extreme heat, closed containers may rupture. Cool containers with flooding quantities of water until after the fire is completely extinguished.

**FIRE FIGHTING PROCEDURES:** This product may release flammable vapors that are slightly heavier than air.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017

Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

**FIRE FIGHTING EQUIPMENT:** As in any fire, wear Self-Contained Breathing Apparatus (SCBA) MSHA/NIOSH approved or equivalent and full protective clothing.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** Avoid run-off into storm drains, ditches and waterways.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Vapors may be heavier than air and will collect in low areas. Containers may be hazardous when empty.

**HANDLING:** Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

**STORAGE:** Keep container closed when not in use. Store in a dry well ventilated area and away from the sun, heat, sparks and open flames. Material will start to cure in the presence of humid air or moisture. Do not store in the same area with oxidizers and amines.

**SHELF LIFE:** 12 months from date of manufacture when stored below 80 F (26.7 C)

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** SM7108  
**Date Revised :** 09/13/2017  
**Revision No :** 19

## PERMATHANE SM7108 Polyurethane Sealant

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Butyl Benzyl Phthalate	<b>OSHA PEL</b>	<b>TWA</b>	NL <sup>[1]</sup>	NL <sup>[1]</sup>
		<b>STEL</b>	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	<b>ACGIH TLV</b>	<b>TWA</b>	NL <sup>[1]</sup>	NL <sup>[1]</sup>
		<b>STEL</b>	NL <sup>[1]</sup>	NL <sup>[1]</sup>
Toluene	<b>OSHA PEL</b>	<b>TWA</b>	200 ppm	NL
		<b>STEL</b>	300 ppm <sup>[2]</sup>	NL <sup>[2]</sup>
	<b>ACGIH TLV</b>	<b>TWA</b>	20 ppm	NL
		<b>STEL</b>	NL <sup>[1]</sup>	NL <sup>[1]</sup>
Toluene Diisocyanate	<b>OSHA PEL</b>	<b>TWA</b>	0.005 ppm	0.04 mg/m <sup>3</sup>
		<b>STEL</b>	0.02 ppm	0.15 mg/m <sup>3</sup>
	<b>ACGIH TLV</b>	<b>TWA</b>	0.005 ppm <sup>[1]</sup>	NL <sup>[1]</sup>
		<b>STEL</b>	0.02 ppm <sup>[1]</sup>	NL <sup>[1]</sup>

**Footnotes:**

1. NL = Not Listed
2. C = Ceiling

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use only in a well ventilated area. To determine exposure levels, monitoring should be performed as outlined by OSHA Standard 29 CFR 1910.1052.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields, goggles or full-face shield as required by 29 CFR 1910.133 - OSHA Eye and Face Protection Standard. A suitable emergency eye wash station and safety shower should be located near the work station.

**SKIN:** Wear chemical resistant, impervious gloves.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017

Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Viscous Liquid**ODOR:** Mild Solvent**COLOR:** Various**pH:** 7.02**PERCENT VOLATILE:** 3.1**Notes:** by weight**FLASHPOINT AND METHOD:** 111.11°C (232°F) ASTM D3278/D3828**FLAMMABLE LIMITS:** N/A to N/A**AUTOIGNITION TEMPERATURE:** Not Determined**VAPOR PRESSURE:** Not Determined**VAPOR DENSITY:** Not Determined**BOILING POINT:** Not Determined**FREEZING POINT:** Not Determined**MELTING POINT:** Not Determined**POUR POINT:** Not Determined**SOLUBILITY IN WATER:** Nonsoluble**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined**EVAPORATION RATE:** Not Determined**DENSITY:** 12.64 lbs/gal**PARTICLE SIZE:** Not Determined**SPECIFIC GRAVITY:** 1.516**VISCOSITY:** Not Determined**MOLECULAR WEIGHT:** Not Determined**(VOC):** 43.1 EPA Method 24 VOC**OXIDIZING PROPERTIES:** Not Determined**WEIGHT PER VOLUME:** Not Determined

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.**STABILITY:** Stable.**CONDITIONS TO AVOID:** Avoid heat, flames, sparks, and other sources of ignition. Keep away from strong oxidizing conditions and agents.**POSSIBILITY OF HAZARDOUS REACTIONS:** None**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide and hydrocarbon fumes if heated to decomposition.**INCOMPATIBLE MATERIALS:** Strong oxidizing agents and amines.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017

Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Butyl Benzyl Phthalate	2330 mg/kg (rats)	> 10000 mg/kg (rabbits)	No data
Toluene	2600 to 7500 mg/kg	12124 mg/kg	8000 ppm (4-hr dose)
Toluene Diisocyanate	4130 to 5110 mg/kg (rats)	> 9400 mg/kg (rabbits)	49 to 5034 ppm (4-hr dose - rat)

#### CARCINOGENICITY

Chemical Name	NTP Status	IARC Status
Toluene		3
Toluene Diisocyanate	2	2B

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Consult with your state and local hazardous waste requirements or guidelines to ensure compliance. Arrange disposal in accordance with EPA, state and local requirements.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated for Transport

**UN/NA NUMBER:** NA

**PACKING GROUP:** NA

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

#### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Environmentally Hazardous Substances, Liquids, N.O.S.

**UN/NA NUMBER:** 3082

**PRIMARY HAZARD CLASS/DIVISION:** 9

**PACKING GROUP:** III

**MARINE POLLUTANT #1:** Butyl Benzyl Phthalate

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** SM7108  
**Date Revised :** 09/13/2017  
**Revision No :** 19

## PERMATHANE SM7108 Polyurethane Sealant

**NOTE: EXCEPTION -** Per IMDG Code 2.10.2.7 - Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less are not subject to any other provisions of the IMDG Code relevant to marine pollutants provided the product is packaged in accordance with the general provisions of the Code.

If single or inner package is < 5 L (1.3 gallons) - ships as Non Hazardous

If single or inner package is > 5 L (1.3 gallons) - ships according to proper shipping description provided above

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

##### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Toluene	2 - 5	108-88-3
Toluene Diisocyanate	1 - 5	26471-62-5

##### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Toluene	2 - 5	1,000 lbs.
Toluene Diisocyanate	1 - 5	100

##### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Butyl Benzyl Phthalate	85-68-7
Toluene	108-88-3
Toluene Diisocyanate	26471-62-5

##### CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Toluene	2 - 5	108-88-3
Toluene Diisocyanate	1 - 5	26471-62-5



# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** SM7108  
**Date Revised :** 09/13/2017  
**Revision No :** 19

## PERMATHANE SM7108 Polyurethane Sealant

### STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Butyl Benzyl Phthalate	Massachusetts Right to Know List New Jersey Right to Know List Pennsylvania Right to Know List
Toluene	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical
Toluene Diisocyanate	Massachusetts Right to Know List New Jersey Right to Know List Pennsylvania Right to Know List

**CALIFORNIA PROPOSITION 65:** This product contains toluene and butyl benzyl phthalate, chemicals known to the state of California to cause birth defects or other reproductive harm.

This product contains traces of Toluene Diisocyanate, a chemical known to the state of California to cause cancer.

Chemical Name	Wt. %	Listed
Butyl Benzyl Phthalate	10 - 20	<ul style="list-style-type: none"> <li>● Developmental Toxicity</li> <li>● Female Reproductive</li> <li>● Male Reproductive</li> </ul>
Toluene	2 - 5	Developmental Toxicity
Toluene Diisocyanate	1 - 5	Cancer

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic



Combustible  
Liquid

### 16. OTHER INFORMATION

**Date Revised:** 09/13/2017

**INFORMATION CONTACT:** (972) 438-9111

**REVISION SUMMARY:** This MSDS replaces the 07/20/2016 MSDS. Revised: **Section 1:** Date Issued.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM7108

Date Revised : 09/13/2017


Revision No : 19

## PERMATHANE SM7108 Polyurethane Sealant

### HMIS RATING

<b>HEALTH</b>	*	<b>1</b>
<b>FLAMMABILITY</b>		<b>2</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children  
For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.